

PIUSI DRUM DISPENSING PACKAGE: 12V DIESEL BI-PUMP WITH K33 METER & NOZZLE

EN. Diesel transfer unit for non commercial use. Easily connected to drums via a quick 2" coupling.

Fitted with a telescopic suction tube for direct connection to fuel drums and nozzle housing located above the drum, near the pump, for easy, clean operations.

Fitted with mechanical meters to ensure precise dispensing and control of single user consumption.

PERFORMANCE

- Flow rate up to 80 l/min
- AC and DC versions available
- Noise level below 75 dB
- Accuracy: +/- 1%

PRODUCTS' RANGE WEIGHT AND PACKAGING

Code without meter	Weight		Packaging		pcs/box
	kg	lbs	mm	inch	
F0022203A	21.6	47.6	480x370x265	18,3x14,6x10,4	1



Fluid Handling Innovation



PRODUCTS' RANGE TECHNICAL DATA

Code without meter	Code with meter	Description	Fluids type	Flow-rate		Voltage			Meter mod.	Nozzle type	Inlet BSP	Hose length
				l/min	gpm	AC V/Hz	Power Watt	Amp. max.				
F0022203A	F0022207A	DRUM BI-Pump 12 V. A120	D	80	21	12V	530	44	K33	A	1"	4 m

476 Boundary Rd
Derrimut
VICTORIA 3030

Phone: (03) 9311 7822
Fax: (03) 9311 8784
E-mail: sales@liquipvictoria.com.au

