# **PIUSI CUBE 70-90 MC 2.0 DIESEL FUEL DISPENSER**

EN. Cube MC 2.0 is equipped with a LAN connection as standard to allow constant dialogue with the software, receive configuration mode data from a remote location and transmit fuel delivery reports.


Cube MC 2.0 can be installed directly on the tank, on a wall or on a pedestal and is the ideal product for those seeking practicality and the maximum safety in diesel fuel dispensing procedures.

The mechanical component of Cube MC 2.0 features:

- High displacement self-priming vane pump. Automatic nozzle with swivel fitting.
- · Integrated nozzle holder with pump start/ stop lever.
- Pump suction mesh strainer.
- Oval gear electronic flow meter

### PERFORMANCE

- Flow rate up to 90 l/min
- Accuracy: +/- 0.5 %
- Continuous AC operation 230 V (mod. 70 MC)
- Duty cycle 30 min DC version (mod. 90 MC)
- Noise level below 75 dB
- IP55 Protection
- LAN adapter




PRODUCTS' RANGE WEIGHT AND PACKAGING										
Code	Wei	ght	Packagin	N. Boxes/ Europallet						
Code	kg	lbs	mm	pcs/ box	×	-				
Column versions										
F00596000	25	55	400x400x460	1	12	24				
F00596100	25	55	400x400x460	1	12	24				







## **SOLUTION FOCUSED SERVICE DRIVEN**





**Self Service** Management 2.0







## ON REQUEST







(10 pcs)







Code **F17299000** Code **F12710120** Code **F12710090** (10 pcs) An hot spot and repeater in case of long distance

#### PRODUCTS' RANGE TECHNICAL DATA

Code	Description	<b>Fluids</b> type	Flow-	gpm	AC V./Hz DC Volt	<b>Power</b> Watt	Amp.	Pump mod.	Meter mod.	<b>Nozzle</b> type	Fil- ter H <sub>2</sub> O filter	Inlet BSP	Self Service Management 2.0
F00596000	Cube 70 MC 2.0	D	70	18	230/50	900	4,9	Panth 72	K600	A60	NO	1"	required
F00596100	Cube 90 MC 2.0	D	90	23,8	230/50	900	4,9	Panth 90	K600	A120	NO	1"	required

48 Vella Drive Sunshine West VICTORIA 3020

Phone: (03) 9311 7822 Fax: (03) 9311 8784

E-mail: sales@liquipvictoria.com.au

